

Technical Data Sheet



Patch

<i>Input</i>	<i>Instrument</i>	<i>Microphone</i>	<i>Insert (F.O.H)</i>
1	Bass drum	AKG D112	Gate + Comp
2	Snare top	SM 57	Comp
3	Snare bottom	BETA 57	Gate
4	Tom	e 604	Gate
5	Floor tom	MD 421	Gate
6	Hi hat	Condenser	
7	Overhead right	Condenser	
8	Overhead left	Condenser	
9	Bass DI	Active DI	Comp
10	Bass mic	MD 421	Comp
11	Guitar 1	SM 57 or MD 441	
12	Guitar 2	SM 57 or MD 421	
13	Lead vocal	Beta 58	Comp
14	Backing vocal	Beta 58	Comp

FOH Technical Data

Indoor venues +/- 15w p/person - outdoor venues +/- 25w p/person
3 ways stereo system (EAW-Nexo-Martin-...) with a graphic EQ 2*31bands
24/8 professional mixing desk (Midas-Allen&Heat-Yamaha-...) + 1 CD player

Group or VCA

1-2 Drum 2 linked compressors
3-4 Bass
5-6 FX (1 reverb room, 1 reverb plate and 1 delay with tap tempo controller)

Monitors Technical Data

6x 1kW wedges with 4*32 bands EQ place such as on the stage map (*)
and similar monitor for the monitor engineer's wedge

HF System headphone for the drummer (if possible)

* Available on the second sheet